Digital library compatibility table

ROOTT NS

V27 v1.0

	Connections	Gap between abutment and the crown, µm[1]	Library selection name	Scanbodies: NSSPCOMIO.01 (Dragon scan)	NSTOM.01	NSTOML.01	Direct scan	NSAM.01	NSANM.01 reverse_scanpost	Rotational option[2]: Fully rotational	Screw channel options: Angulated 0-20°	Analog: NSANM.01
	NSPCOMR.01	Ordinary - 35 Pro - 25, 35, 50, 70, 90, 110	ROOTT ® NS V27 ROOTT ® NS V27 Pro	●	●	●	●	●	●	●	●	●
	Direct flat (SNZF.01)	Ordinary - 15 Pro - 0, 15, 25, 35		●	●	●	●	●	●	●	●	●
	Direct cone (SNZC.01)			●	●	●	●	●	●	●	●	●
	NSAM.01 [3]	Ordinary - 35 Pro - 25, 35, 50, 70, 90, 110		●	●	●	●	●	●	●		●

Notes:
Names - number after dot means product version.

[1] There are 2 types of libraries: Ordinary - each abutment has only one choice.
Pro - each abutment have different choices for different cement gaps.

[2] Possible abutment rotational change.

[3] NSAM abutment is available in six different heights (mm): 3.12, 4.5, 6.05, 7.6, 9.16 and full part is 11.25. Shortest vesion of NSAM (3.12mm) has angled screwchannel option.

