Digital library compatibility table, 2025

ROOTT M P Viper

[1] Possible abutment rotational change
[2] AM.05.V is available in six different heights: 3.5, 5.05, 6.6, 8.15, 9.7, 11.25

Connections	Screw included	25, 35, 50, 70, 90, 110 µm gap between abutment and crown	Library selection name	AM.05.V[2]	SPCOMIO.04.V	SPCOMS.05	SPCOMS.06	SPCOMIOS.02	SPCOMIOS.03	TOM.05.V	TOML.04.V	Direct scan	ANM.05.V (reverse scan post)	Rotational option[1]		Angulated 0-20°
														Fully rotational	Rotation every 60°	
AM.05.V[2]	●	●	TRATE® ROOTT® M, P Viper	●	●	●	●	●	●	●	●	●	●	●		
Direct on implant		●		●	●	●	●	●	●	●	●	●	●	●		●
PCOM.05.V	●	●		●	●	●	●	●	●	●	●	●	●		●	●
PCOM.05.V (rotational)	●	●		●	●	●	●	●	●	●	●	●	●	●		
PCOMR.01.V	●	●		●	●	●	●	●	●	●	●	●	●	●		●
PCOMS.04	●	●		●	●	●	●	●	●	●	●	●	●	●		●
PCOMS.04 (rotational)	●	●		●	●	●	●	●	●	●	●	●	●	●		